

TSL-570

High Performance Tunable Laser



Features

- Fast, up to 200 nm/s, wavelength sweeps
- Wide tuning range lineup: 1240 to 1680 nm
- Wavelength resolution: 0.1 pm
- High signal-to-noise ratio: 90 dB/0.1 nm
- Fine tuning scan range: 10 GHz



Applications

- Optical component characterization
- Fiber optic transmission testing
- Photonic material characterization
- Optical spectroscopy


Product Overview

The all-new TSL-570 capitalizes on Santec's 33 years of experience in tunable laser manufacture. The TSL-570 is a high performance tunable laser with a wide tuning range and an output combining high power and high signal-to-noise ratio. It uses a new optical cavity design with precise speed control up to 200 nm/s and sub-picometer resolution and accuracy.


Tunable lasers are used extensively in photonics; for optical component characterization, photonic integrated circuit testing, quantum photonics, spectroscopy and sensors. Santec's TSL-570 is a high specification, full feature instrument suitable for all applications. It has a simple to use touch panel display as well as Ethernet, GPIB and USB interfaces for remote control. A Wake-on-LAN (WoL) feature provides convenience for remote installations. Models are available to cover from 1240 to 1680 nm with output powers up to 20 mW.

Santec's new sealed laser cavity is mode-hop-free and provides a stable output at every wavelength. It has 0.1 pm resolution, sub-pm accuracy and a market leading 90 dB/0.1 nm, ultra-low level of spontaneous source emission. The TSL-570 integrates seamlessly with Santec's optical power meters, optical switches and polarization controllers creating benchmark, turn-key solutions for wavelength dependent loss (WDL) and polarization dependent loss (PDL) measurements.

Wavelength Stability



Temperature Dependency of Wavelength Variation



Model Selection

Model Number	Wavelength Range
260360	1260 — 1360
240380	1240 — 1380
355485	1355 — 1485
355505	1355 — 1505
500630	1500 — 1630
480640	1480 — 1640
560680	1560 — 1680

Other wavelength range model is available on request. Please contact santec sales.

Laser Safety Information



This product is classified class 1M laser product according to IEC 60825-1 (2014).

This product complies with FDA performance standards for laser products except for deviations pursuant to Laser Notice No. 56 dated May 8, 2019.

TSL-570 Optical Specifications

Wavelength Characteristics

Parameter	Unit	Performance						
		Type A	Type C	Type P				
Wavelength Tuning Range ⁸	nm	1240 - 1380 / 1355 - 1505 / 1480 - 1640						
Wavelength Setting Resolution	pm	0.1						
Wavelength Stability (typ.) ¹	pm	≤ ±5	≤ ±1	≤ ±1				
Absolute Wavelength Accuracy ²	Step Mode	pm	±15	±3	±1 (typ.)			
Absolute Wavelength Accuracy (Operating temp.)						±20	±5	±2
Wavelength Repeatability (typ.)						±5	±1	±0.5
Absolute Wavelength Accuracy (typ.) ²	Continuous sweep mode @100 nm/s	pm	±15	±5	±1.5			
Wavelength Repeatability (typ.)						±8	±1	±0.8
Sweep Speed	nm/s	1 to 200						
Fine Tuning Scan Range	GHz	≥10						

Optical Power Characteristics

Parameter	Unit	Performance		
		Type A	Type C	Type P
Output Power ⁷	Peak (typ.)	dBm		
	@ 1260-1360 / 1380-1485 / 1500-1630 nm	dBm		
	Full Tuning Range	dBm		
Power Stability ^{1,3}	dB	±0.01		
Power Repeatability ³	dB	±0.01		
Power Flatness vs. Wavelength ^{3,7}	Step mode	dB		
Dynamic Power Repeatability (typ.) ³	Continuous sweep mode @100 nm/s	dB		
Dynamic Relative Power Flatness (typ.) ³		dB		
Relative Intensity Noise (RIN) (typ.) ⁴	dB/Hz	-145 (1 MHz to 3 GHz)		

Spectrum

Parameter	Unit	Performance		
		Type A	Type C	Type P
Linewidth (typ.)	Coherence Ctrl. Off	kHz		100
	Coherence Ctrl. On	MHz		
SMSR (typ.)	dB	≥45		
Signal to Total Source Spontaneous Emission Ratio ⁵	dB	≥70		
Signal to Source Spontaneous Emission Ratio ⁶	dB/nm	≥80 (≥90 dB/0.1 nm)		

Notes:

All specifications are quoted after 1 hour warm-up period. Specifications apply for wavelengths not equal to any water absorption line.

¹ For period of 1 hour. Within ± 0.5 °C.

² At 25±1 °C.

³ At "Auto" power mode and > 0 dBm.

⁴ At maximum output power.

⁵ Ratio of signal power to total spontaneous emission power within ±15 nm of the signal wavelength (typical value).

⁶ Ratio of signal power to maximum spontaneous emission power in a 1 nm band within a ±3 nm band around the signal wavelength (typical value).


⁷ The specification range is up to 1630 nm.

⁸ Full wavelength tuning range reduced by 2 nm on both ends for sweep speeds ≥ 100 nm/s and < 150 nm/s.


Full wavelength tuning range reduced by 3 nm on both ends for sweep speeds ≥ 150 nm/s.

TSL-570 Typical Configuration

IL / PDL measurement setup with the polarization controller PCU-110 and the power meter MPM-210H



IL measurement setup with the power meter MPM-210H



Ordering Scheme & Instructions

1. Configure TSL High Performance Tunable Laser

TSL-570- [] - [] [] [] [] [] - P - [] - [] [] - 00-1

TYPE	
A	Type A
C	Type C
P	Type P

SOURCES	
260360	1260-1360
240380	1240-1380
355485	1355-1485
355505	1355-1505
500630	1500-1630
480640	1480-1640
560680	1560-1680

FIBER TYPE	
P	PMF

CONNECTOR POLISH	
SP	SPC
AP	APC

CONNECTOR TYPE	
F	FC
S	SC

TSL-570 Specification (Swept Test System with TSL-570)

Parameter	Unit	Specification			Notes
		Type A	Type C	Type P	
Wavelength Accuracy (typ.) (Absolute) ¹	pm	±12	±2.5	±1.0	at 50 nm/s
		±15	±3.5	±1.5	at 100 nm/s
		±17	±4.5	±2.1	at 200 nm/s
Wavelength Accuracy (typ.) (Relative)	pm	±9	±2.2	±0.8	at 50 nm/s
		±12	±3.0	±1.3	at 100 nm/s
		±14	±4.0	±1.9	at 200 nm/s
Wavelength Repeatability ²	pm	±5	±1.2	±0.5	at 50 nm/s
		±6	±1.5	±0.8	at 100 nm/s
		±8	±2.0	±1.1	at 200 nm/s
Tunable Laser		Type A, Type C and Type P			
Power Meter Module		MPM-211, 212	MPM-215		
Scan Speed	nm/s	1 to 200			
Dynamic Range for Insertion Loss at one scan (typ.)	dB	40	60		
Dynamic Range for Insertion Loss at two scans (typ.)	dB	75	-		
Dynamic Range for PDL (typ.)	dB	0 to 5			
Measurement Time for IL (typ.) ³	sec	3@100 nm/s, 1.8@200 nm/s			
Measurement Time for IL / PDL (typ.) ³	sec	12@100 nm/s, 6.8@200 nm/s			
Wavelength Resolution	pm	0.1			
IL Accuracy (typ.)	dB	±0.02	±0.02	0 to 30 dB Device IL	
		±0.1	±0.02	30 to 40 dB Device IL	
		±0.1	±0.05	40 to 60 dB Device IL	
IL Repeatability (typ.) ^{2,4}	dB	±0.02			
IL Resolution	dB	0.001			
PDL Accuracy (typ.)	dB	±(0.02 + 3% of PDL)	±(0.02 + 3% of PDL)	0 to 20 dB Device IL	
		±(0.15 + 3% of PDL)		20 to 40 dB Device IL	
PDL Repeatability (typ.) ^{2,4}	dB	±0.03			
PDL Resolution	dB	0.01			
Communication	-	USB (USB 2.0 High Speed)		MPM-210H	
		GP-IB (IEEE488.2), Ethernet		PCU-110 / MPM-210H	
Operating Temperature	°C	15 to 35			
Operating Humidity	%	< 80			

Notes:

All specifications are quoted after 1 hour warm-up period and executing a zero calibration.

¹ Temperature within 25±5 °C

² Temperature within 25±1 °C

³ The measurement condition is within wavelength resolution 5 pm, wavelength range 100 nm, one scan for 1 channel.

⁴ Does not include influence of connector.

TSL-570 General Specifications

Category	Parameter	Unit	Performance	
Interface	Optical Output Connector	-	FC or SC, SPC or APC	
	Optical Fiber	-	PMF ¹	
	Communication	-	GP-IB (IEEE 488.2), USB, Ethernet	
	Power Monitor	V	0 to 3	
Modulation	Intensity Modulation	kHz	DC to 400 (Input level -2 to 0 V, Modulation depth > 50 %/V (typ.))	
Environmental Conditions and Others	Operating	Temperature	°C	15 to 35
		Humidity	%	< 80 (non-condensing)
	Power Supply	-	AC100 to 120 / 200 to 240 V ±10 %, 50/60 Hz	
	Power Consumption	VA	100	
	Dimensions (W) x (D) x (H) ²	mm	220 x 385 x 130	
Weight	kg	7		

Notes:

¹ In case of PMF, polarization axis in alignment with connector key. Polarization extinction ratio is 17 dB (typical value).

² Except for the protrusion.



Santec Regional Sales Offices

SANTEC CORPORATION

5823 Ohkusa-Nenjozaka, Komaki, Aichi, 485-0802, Japan
Tel: +81-568-79-3536 | Fax: +81-568-79-1718

Santec Europe Ltd.

99 Park Drive, Milton Park, Abingdon, Oxfordshire, OX14 4RY, United Kingdom
Tel: +44-20-3176-1550

SANTEC U.S.A. CORPORATION

433 Hackensack Ave., Hackensack, NJ, 07601, USA. Toll Free: +1-800-SANTEC1 (726-8321)
Tel: +1-201-488-5505 | Fax: +1-201-488-7702

Santec (Shanghai) Corporation Limited

21F Room H, Hua Du Bldg., No.838 Zhangyang Road, Pudong District, Shanghai, 200122, China
Tel: +86-21-5836-1261 | Fax: +86-21-5836-1263

2022© SANTEC CORPORATION Santec reserves the right to make changes in equipment design, components or specifications without notice.

TSL-570-C-E/Ver.3.0 CODE-202303-TM-KT-CPY